

Hedonic seat arrangement problems

Citation for published version (APA):

Bodlaender, H. L., Hanaka, T., Jaffke, L., Ono, H., Otachi, Y., & van der Zanden, T. C. (2020). Hedonic seat arrangement problems. In B. An, A. El Fallah Seghrouchni, & G. Sukthankar (Eds.), *Proceedings of the 19th International Conference on Autonomous Agents and Multiagent Systems, AAMAS 2020* (Vol. 2020-May, pp. 1777-1779). International Foundation for Autonomous Agents and Multiagent Systems (IFAAMAS). <https://dblp.org/db/conf/atal/aamas2020.html>

Document status and date:

Published: 01/01/2020

Document Version:

Publisher's PDF, also known as Version of record

Document license:

Taverne

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.umlib.nl/taverne-license

Take down policy

If you believe that this document breaches copyright please contact us at:

repository@maastrichtuniversity.nl

providing details and we will investigate your claim.

Hedonic Seat Arrangement Problems*

Extended Abstract

Hans L. Bodlaender
Utrecht University
Utrecht, The Netherlands
h.l.bodlaender@uu.nl

Tesshu Hanaka
Chuo University
Tokyo, Japan
hanaka.91t@g.chuo-u.ac.jp

Lars Jaffke
University of Bergen
Bergen, Norway
lars.jaffke@uib.no

Hirota Ono
Nagoya University
Nagoya, Japan
ono@i.nagoya-u.ac.jp

Yota Otachi
Kumamoto University
Kumamoto, Japan
otachi@cs.kumamoto-u.ac.jp

Tom C. van der Zanden
Maastricht University
Maastricht, The Netherlands
T.vanderZanden@
maastrichtuniversity.nl

ABSTRACT

In this paper, we study a variant of hedonic games, called SEAT ARRANGEMENT. The model is defined by a bijection from agents with preferences to vertices in a graph. The utility of an agent depends on the neighbors in the graph. In this paper, we study the price of stability and fairness in SEAT ARRANGEMENT, and the computational complexity and the parameterized complexity of finding certain “good” seat arrangements, say MAXIMUM WELFARE ARRANGEMENT, MAXIMIN UTILITY ARRANGEMENT, STABLE ARRANGEMENT, and ENVY-FREE ARRANGEMENT.

KEYWORDS

hedonic game; stability; envy-freeness; computational complexity; parameterized complexity; local search

ACM Reference Format:

Hans L. Bodlaender, Tesshu Hanaka, Lars Jaffke, Hirota Ono, Yota Otachi, and Tom C. van der Zanden. 2020. Hedonic Seat Arrangement Problems. In *Proc. of the 19th International Conference on Autonomous Agents and Multiagent Systems (AAMAS 2020), Auckland, New Zealand, May 9–13, 2020*, IFAAMAS, 3 pages.

1 INTRODUCTION

Given a set of n agents with preferences for each other and an n -vertex graph, called the *seat graph*, we consider to assign each agent to a vertex in the graph. Each agent has a utility that depends on the agents assigned to neighbors vertices in the graph. Intuitively, if a neighbor is preferable for the agent, his/her utility is high. This models several situations such as seat arrangements in classrooms, offices, restaurants, or vehicles. Here, a vertex corresponds to a seat and an assignment corresponds to a seat arrangement. If we arrange seats in a classroom, the seat graph is a grid. As another example, if we consider a round table in a restaurant, the seat graph is a cycle. We name the model SEAT ARRANGEMENT.

*The full version of this paper is available in [5]. This work is partially supported by JSPS KAKENHI Grant Numbers JP17K19960, JP17H01698, JP18H04091, JP18K11168, JP18K11169, JP19K21537.

Proc. of the 19th International Conference on Autonomous Agents and Multiagent Systems (AAMAS 2020), B. An, N. Yorke-Smith, A. El Fallah Seghrouchni, G. Sukthankar (eds.), May 9–13, 2020, Auckland, New Zealand. © 2020 International Foundation for Autonomous Agents and Multiagent Systems (www.ifaamas.org). All rights reserved.

SEAT ARRANGEMENT is related to hedonic games [7]. If the seat graph in a Seat Arrangement instance is a disjoint union of cliques, then each clique may be viewed as a potential coalition. Hence an arrangement on that graph naturally corresponds to a coalition forming. In that sense, this model is considered a hedonic game of arrangement on topological structures.

In this paper, we consider the following problems to find four types of *desirable* seat arrangements: MAXIMUM WELFARE ARRANGEMENT (MWA), MAXIMIN UTILITY ARRANGEMENT (MUA), STABLE ARRANGEMENT (STA), and ENVY-FREE ARRANGEMENT (EFA). MWA is the problem to find a seat arrangement that maximizes the sum of utilities of agents, which is called the *social welfare*.

The concept of MWA is a macroscopic optimality, and hence it may ignore individual utilities. Complementarily, MUA is the problem to find a seat arrangement that maximizes the least utility of an agent. From the viewpoint of economics, the maximin utility of an arrangement can be interpreted as a measure of fairness [3, 10, 18].

Stability is one of the central topics in the field of hedonic games including STABLE MATCHING [2, 7, 14, 19]. Motivated by this, we define a *stable* arrangement as an arrangement with no pair of agents that has an incentive of swapping their seats (i.e., vertices), called a *blocking pair*. This corresponds to the definition of *exchange-stability* proposed by Alcalde in the context of stable matchings [1]. In SEAT ARRANGEMENT, STA is the problem of deciding whether there is a stable arrangement in a graph.

Finally, we consider the envy-freeness of SEAT ARRANGEMENT. The envy-freeness is also a natural and well-considered concept in hedonic games.

2 THE MODEL

Let $G = (V, E)$ be a graph where $n = |V|$ and $m = |E|$. We denote by \mathbf{P} the set of agents, and define an *arrangement* as follows.

Definition 2.1 (Arrangement). For a set of agents \mathbf{P} and a graph G , a bijection $\pi : \mathbf{P} \rightarrow V(G)$ is called an *arrangement* in G .

We denote by Π the set of all arrangements in G . Note that $|\Pi| = n!$. We call graph G the *seat graph*.

Definition 2.2 ((p, q) -swap arrangement). For a pair of agents $p, q \in \mathbf{P}$, we say that π' is the (p, q) -swap arrangement if π' can be obtained from swapping the arrangement of p and q .

Next, we define the *preference* of an agent.

Definition 2.3 (Preference). The *preference* of $p \in \mathbf{P}$ is defined by $f_p : \mathbf{P} \setminus \{p\} \rightarrow \mathbb{R}$.

We denote by $\mathcal{F}_{\mathbf{P}}$ the set of preferences of all agents in \mathbf{P} . Here, we say the preferences are *binary* if $f_p : \mathbf{P} \setminus \{p\} \rightarrow \{0, 1\}$ for every agent p , are *nonnegative* if $f_p : \mathbf{P} \setminus \{p\} \rightarrow \mathbb{R}_0^+$, and are *positive* if $f_p : \mathbf{P} \setminus \{p\} \rightarrow \mathbb{R}^+$. Furthermore, we say they are *symmetric* if $f_p(q) = f_q(p)$ holds for any pair of agents $p, q \in \mathbf{P}$ and *strict* if for any $p \in \mathbf{P}$ there is no pair of distinct $q, r \in \mathbf{P}$ such that $f_p(q) = f_p(r)$.

Finally, we define the *utility* of an agent and the *social welfare* of an arrangement π .

Definition 2.4 (Utility and social welfare). Given an arrangement π and the preference of p , the *utility* of p is defined by $U_p(\pi) = \sum_{v \in N(\pi(p))} f_p(\pi^{-1}(v))$. Moreover, the *social welfare* of π for \mathbf{P} is defined by the sum of all utilities of agents and denoted by $\text{sw}(\pi) = \sum_{p \in \mathbf{P}} U_p(\pi)$.

We define four types of SEAT ARRANGEMENT problems. An arrangement π^* is *maximum* if it satisfies $\text{sw}(\pi^*) \geq \text{sw}(\pi)$ for any arrangement π . Also, an arrangement π^* is a *maximin* arrangement if π^* satisfies $\min_{p \in \mathbf{P}} U_p(\pi^*) \geq \min_{p \in \mathbf{P}} U_p(\pi)$ for any arrangement π . Then, MAXIMUM WELFARE ARRANGEMENT (MWA) and MAXIMIN UTILITY ARRANGEMENT (MUA) are the problems to find a maximum (maximin) arrangement in G .

Next, we define the *stability* and the *envy-freeness* of SEAT ARRANGEMENT.

Definition 2.5 (STABILITY). Given an arrangement π , a pair of agents p and q is called a *blocking pair* for π if it satisfies that $U_p(\pi') > U_p(\pi)$ and $U_q(\pi') > U_q(\pi)$ where π' is the (p, q) -swap arrangement for π . If there is no blocking pair in π , it is said to be *stable*.

Definition 2.6 (ENVY-FREE). An arrangement π is *envy-free* if there is no agent p such that there exists $q \in \mathbf{P} \setminus \{p\}$ that satisfies $U_p(\pi') > U_p(\pi)$ where π' is the (p, q) -swap arrangement for π .

STABLE ARRANGEMENT (STA) and ENVY-FREE ARRANGEMENT (EFA) are the problems to decide whether there is a stable (envy-free) arrangement in G .

3 OUR CONTRIBUTION

In this paper, we first investigate the price of stability (PoS) and the price of fairness (PoF) of SEAT ARRANGEMENT, which are defined as the ratio of the maximum social welfare over the social welfare of a maximum stable solution and a maximin solution, respectively. For the price of stability, we can say the PoS is 1 under symmetric preferences by a result in [17]. For the price of fairness, we show that there is a family of instances such that PoF is unbounded. For the binary case, we show an upper bound of $\tilde{d}(G)$ of PoF, where $\tilde{d}(G)$ is the average degree of the seat graph G . On the other hand, we present an almost tight lower bound $\tilde{d}(G) - 1/4$ of PoF. Furthermore, we give a lower bound $\tilde{d}(G)/2 + 1/12$ for the cases with symmetric preferences.

Next, we give dichotomies of computational complexity of four SEAT ARRANGEMENT problems from the perspective of the maximum order of connected components in the seat graph. For MWA,

MUA, and symmetric EFA, we show that they are solvable in polynomial time if the order of each connected component in the seat graph is at most 2 whereas they are NP-hard even if the order of each connected component of the seat graph is 3. Since a maximum arrangement is always stable under symmetric preferences, symmetric STA can also be solved in polynomial time if the order of each connected component is at most 2. On the other hand, STA is NP-complete even if the order of each connected component in the seat graph is at most 2. Note that if each connected component in the seat graph is of order at most 1, it consists of only isolated vertices, and hence STA is trivially solvable.

For the parameterized complexity, we show that MWA can be solved in time $n^{O(\gamma)}$ whereas it is W[1]-hard with respect to vertex cover number γ of the seat graph and cannot be solved in time $n^{o(n)}$ and $f(\gamma)n^{o(\gamma)}$ under ETH. Moreover, we prove that MUA and symmetric EFA are weakly NP-hard even on seat graphs with $\gamma = 2$.

Finally, we study the parameterized complexity of local search of finding a stable arrangement. We show that determining whether a stable arrangement can be obtained from a given arrangement by k swaps is W[1]-hard when parameterized by $k + \gamma$, whereas it can be solved in time $n^{O(k)}$.

4 RELATED WORK

A *hedonic game* is a non-transferable utility game regarding coalition forming, where each agent's utility depends on the identity of the other agents in the same coalition [6, 11]. It includes the STABLE MATCHING problem [7]. SEAT ARRANGEMENT can be considered a hedonic game of arrangement on a graph.

Several graph-based variants of hedonic games have been proposed in the literature, see e.g. [2, 8, 9, 12, 16]. However, they typically utilize graphs to define the preferences of agents, and both the preferences and coalitions define the utilities of agents. On the other hand, in SEAT ARRANGEMENT, the preferences are defined independently of a graph and the utility of an agent is determined by an arrangement in a graph (more precisely, the preferences for the assigned neighbors in the graph).

A major direction of research about hedonic games is the computational complexity of finding desirable solutions such as a solution with maximum social welfare and a stable solution [2, 6]. Peters [20] and Hanaka et al. [15] investigate the parameterized complexity of hedonic games for several graph parameters (e.g., treewidth). For the local search complexity, Gairing and Savani study the PLS-completeness of finding a stable solution [12, 13]. In terms of mechanism design and algorithmic game theory, many researchers study the price of anarchy, the price of stability, and the price of fairness [3, 4, 7, 19].

Very recently, in the context of one-sided markets, Massand and Simon consider the problem of allocating indivisible objects to a set of rational agents where each agent's final utility depends on the intrinsic valuation of the allocated item as well as the allocation within the agent's local neighbourhood [17]. Although the problem is motivated from different contexts, it has a quite similar nature to SEAT ARRANGEMENT, and they also considered stable and envy-free allocation on the problem.

REFERENCES

- [1] J. Alcalde. 1994. Exchange-proofness or divorce-proofness? Stability in one-sided matching markets. *Economic design* 1, 1 (1994), 275–287.
- [2] H. Aziz, F. Brandt, and H. G. Seedig. 2013. Computing desirable partitions in additively separable hedonic games. *Artificial Intelligence* 195 (2013), 316 – 334.
- [3] D. Bertsimas, V.F. Farias, and N. Trichakis. 2011. The Price of Fairness. *Operations Research* 59, 1 (2011), 17–31.
- [4] V. Bilò, A. Fanelli, M. Flammini, G. Monaco, and L. Moscardelli. 2018. Nash Stable Outcomes in Fractional Hedonic Games: Existence, Efficiency and Computation. *J. Artif. Intell. Res.* 62 (2018), 315–371.
- [5] Hans L. Bodlaender, Teshu Hanaka, Lars Jaffke, Hirotaka Ono, Yota Otachi, and Tom C. van der Zanden. 2020. Hedonic Seat Arrangement Problems. (2020). arXiv:cs.GT/2002.10898
- [6] A. Bogomolnaia and M. O. Jackson. 2002. The Stability of Hedonic Coalition Structures. *Games and Economic Behavior* 38, 2 (2002), 201 – 230.
- [7] F. Brandt, V. Conitzer, U. Endriss, J. Lang, and A. D. Procaccia. 2016. *Handbook of Computational Social Choice* (1st ed.). Cambridge University Press, New York, NY, USA.
- [8] S. Brânzei and K. Larson. 2009. Coalitional Affinity Games and the Stability Gap. In *IJCAI 2009*. 79–84.
- [9] S. Brânzei and K. Larson. 2011. Social Distance Games. In *IJCAI 2011*. 91–96.
- [10] I. Caragiannis, C. Kaklamanis, P. Kanellopoulos, and M. Kyropoulou. 2012. The Efficiency of Fair Division. *Theory of Computing Systems* 50, 4 (2012), 589–610.
- [11] J. H. Dréze and J. Greenberg. 1980. Hedonic Coalitions: Optimality and Stability. *Econometrica* 48, 4 (1980), 987–1003.
- [12] M. Gairing and R. Savani. 2010. Computing Stable Outcomes in Hedonic Games. In *SAGT 2010*. 174–185.
- [13] M. Gairing and R. Savani. 2011. Computing stable outcomes in hedonic games with voting-based deviations. In *AAMAS 2011*. 559–566.
- [14] D. Gale and L. S. Shapley. 1962. College Admissions and the Stability of Marriage. *The American Mathematical Monthly* 69, 1 (1962), 9–15.
- [15] T. Hanaka, H. Kiya, Y. Maei, and H. Ono. 2019. Computational Complexity of Hedonic Games on Sparse Graphs. In *PRIMA 2019*. 576–584.
- [16] A. Igarashi and E. Elkind. 2016. Hedonic Games with Graph-restricted Communication. In *AAMAS 2016*. 242–250.
- [17] Sagar Massand and Sunil Simon. 2019. Graphical One-Sided Markets. In *IJCAI-19*. International Joint Conferences on Artificial Intelligence Organization, 492–498.
- [18] N. Nguyen, A. Rey, L. Rey, J. Rothe, and L. Schend. 2016. Altruistic Hedonic Games. In *AAMAS 2016*. 251–259.
- [19] N. Nisan, T. Roughgarden, E. Tardos, and V. V. Vazirani. 2007. *Algorithmic Game Theory*. Cambridge University Press, Cambridge.
- [20] D. Peters. 2016. Graphical Hedonic Games of Bounded Treewidth. In *AAAI 2016*. 586–593.