

# Submillimeter T2 weighted BOLD fMRI of human visual cortex

## Citation for published version (APA):

Kemper, V. G. (2016). *Submillimeter T2 weighted BOLD fMRI of human visual cortex*. Maastricht University.

## Document status and date:

Published: 01/01/2016

## Document Version:

Publisher's PDF, also known as Version of record

## Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

## General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

[www.umlib.nl/taverne-license](http://www.umlib.nl/taverne-license)

## Take down policy

If you believe that this document breaches copyright please contact us at:

[repository@maastrichtuniversity.nl](mailto:repository@maastrichtuniversity.nl)

providing details and we will investigate your claim.

## Propositions of the thesis

### Submillimeter $T_2$ weighted BOLD fMRI of human visual cortex

Valentin G. Kemper, Maastricht, April 21, 2016

1. A deeper understanding of the functional organization within cortical areas would be highly desirable resolving the debate about the cortical column as a basic functional processing unit. If ever achievable, this goal will require a joint effort of various neuroimaging modalities, and modeling approaches.
2. Ultra-high field high spatial resolution functional MRI is an essential tool in bridging the gap between brain macro- and microscale topography. Recent examples in the visual domain are ocular dominance, orientation, axis of motion, disparity, and color selectivity.
3. 3D-GRASE has less  $T_2^*$  contamination in  $T_2$  weighted fMRI than large field of view 2D SE-EPI (in practical experiments), and hence better functional specificity. However, blurring in partition direction may be critically strong.
4. The variable flip angle approach can reduce the slice blurring in 3D-GRASE at little to no cost in terms of functional sensitivity. It can also be employed to increase the imaging coverage.
5. High resolution  $T_2$  weighted fMRI at 9.4 Tesla of early visual cortex is possible even without the application of subject-specific parallel transmission RF pulses.
6. The retinotopical boundary of primary visual cortex to secondary visual cortex corresponds well to the seizing observation of the Stria Gennari in  $T_2^*$  weighted cortical depth profiles.
7. Submillimeter spatial resolution and cortical depth specificity may allow investigation of informational flow between cortical areas. Local microcircuitry must be taken into account carefully in the analysis.
8. The degree to which the methodological knowledge from this thesis can be “valorized” in other applications scales inversely with their “methodical distance” from it, and is theoretically infinite ( $\int_{\mathbb{R}^+} 1/x \, dx = \infty$ ).
9. The term “raw data” may refer to various stages of the processing chain of fMRI data depending on the scientific interest and background of the communicator.